

TREMstop Putty

A Firestopping Putty Stick

PRODUCT DESCRIPTION:

TREMstop Putty is a moldable, intumescent putty available in easy-to-use stick form for electrical applications. TREMstop Putty exhibits great adhesion and remains pliable allowing for easy retrofit. TREMstop Putty is applied by hand allowing for quick installation. TREMstop Putty also reduces sound transmission through assemblies.

Also available is the TREMstop MP, a moldable, putty pad specifically designed to fit a common 4 in. x 4 in. (10.2 cm x 10.2 cm) metal electrical outlet box.

ADVANTAGES:

- Remains highly pliable permitting easy retrofits
- Excellent adhesive strength
- Application by hand makes installation fast and easy
- Hands can be cleaned with soap and water
- Reduces sound transmission through wall assemblies
- Listed up to a 4 hour fire rating

BASIC USES:

Penetrations

- EMT pipe
- Conduits
- Cables
- Cable trays

Building Assemblies

- Concrete wall or floor
- Gypsum wallboard
- Hollowcore concrete

PHYSICAL PROPERTIES:

Color: Grey

Odor: None

STC Information:
(ASTM E-90)

Evaluated to restore STC ratings of construction assemblies with STC ratings up to 51

VOC (g/l) : 0

PACKAGING:

2.5 in. x 13.5 in. (66.2 in.³) stick
(6.4 cm x 34.3 cm) (1102.8 cm³)

Weight: 52 ounces/per stick
12/case

*STC evaluated in accordance with ASTM E-90.
**Expected STC based on extrapolation of data.

TREMstop Putty

A Firestopping Putty Stick

INSTALLATION TECHNIQUES:

Refer to the Tremco Firestopping Products & Systems guide for firestop systems.

Tear off an adequate amount of putty to fill the void. Knead in hands to make pliable before applying to the void, gap or surface. Putty can be removed and repositioned.

LIMITATIONS:

- Not recommended for use in passive fire containment systems not listed or approved by Tremco.
- Not recommended for exterior applications.

APPLICABLE TEST STANDARDS:

UL 1479 (ASTM E-814)
UL 263 (ASTM E-119)
CAN4-S115M
CAN/ULC-S101M

WARRANTY:

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

TECHNICAL SERVICES

For more information, contact technical services:

Toll free: (866) 209-2404
Fax: (216) 514-7575
E-mail: FireTech@tremcoinc.com

ORDER PLACEMENT:

To place an order, contact customer service:

United States: (800) 321-7906
Canada: (800) 363-3213

THE TREMCO FAMILY OF PRODUCTS IS RECOGNIZED BY



Tremco Incorporated • 3735 Green Road • Beachwood, Ohio 44122 USA
Phone: (216) 292-5000 • Fax: (216) 514-7575 • Toll Free: (866) 209-2404

Tremco Canada Division • 215 Wicksteed Ave. • Toronto, Ontario M4H 1G7 Canada
Phone: (416) 467-2455 • Fax: (800) 361-3514 • Toll Free: (800) 363-3213

For MSDS or additional Spec Data Sheets, contact customer service at
(800) 321-7906 or visit www.tremcofirestop.com

TREMCO