

TREMstop Strap

A Convenient, One-Piece Flexible Intumescent Strap for Plastic Pipe

PRODUCT DESCRIPTION:

TREMstop Strap is a state-of-the art system that provides easily installed firestopping for your closed or vented plumbing system. This new intumescent strap can be used in place of a traditional firestopping collar device. It is simple to install by wrapping the strap around the pipe, fastening the ends to each other with the attached tab and sliding it into place within the annular space. This easily installed system does not require fasteners reducing installation time. Available for 1½ in., 2 in., 3 in. and 4 in. diameter pipes for most nonmetallic penetrations.

ADVANTAGES:

- One-piece flexible intumescent strap is easily applied in seconds around a nonmetallic pipe penetration through a fire-rated floor or wall assembly.
- Can be installed during the rough-in-stage or as a retrofit.
- Available for 1½ in., 2 in., 3 in. and 4 in. diameter pipes
- Does not require special tools or compaction of mineral wool or backer material
- Extremely environmentally stable and resistant to humidity and/or immersion in water
- Easily installed from the top or bottom of a slab and tucked into the opening.
- Listed up to a 2 hour fire rating

BASIC USES:

Penetration

- PVC and ccPVC
- ABS and ccABS
- CPVC
- FRPP

Building Assemblies

- Concrete floors or walls
- Hollow core concrete
- Fluted metal deck
- Gypsum wallboard
- Wood floor/ceiling

PHYSICAL PROPERTIES:

Nominal Size	Overall Length — in. (cm)
1½ in.	Approximately 9 ⁷ / ₈ (25)
2 in.	Approximately 11 ⁷ / ₈ (30)
3 in.	Approximately 16 (40.6)
4 in.	Approximately 20 ³ / ₄ (52.7)

- Resistant to humidity and/or immersion in water

PACKAGING:

1½ in. TREMstop Strap	36/case
2 in. TREMstop Strap	36/case
3 in. TREMstop Strap	24/case
4 in. TREMstop Strap	16/case

TREMstop Strap

A Convenient, One-Piece Flexible Intumescent Strap for Plastic Pipe

INSTALLATION TECHNIQUES:

Refer to the Tremco Firestopping Products & Systems guide for firestop systems.

Select the proper TREMstop Strap for the pipe application based on the size and type, along with the fire rating and construction of the floor or wall assembly being penetrated.

Wrap the TREMstop Strap around the pipe and fasten using the integral adhesive strip. Slide into annular space.

APPLICABLE TEST STANDARDS:

UL 1479 (ASTM E-814)

CAN4-S115M including 50pa Positive Pressure for DWV piping

WARRANTY:

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

TECHNICAL SERVICES

For more information, contact technical services:

Toll free: (866) 209-2404

Fax: (216) 514-7575

E-mail: FireTech@tremcoinc.com

ORDER PLACEMENT:

To place an order, contact customer service:

United States: (800) 321-7906

Canada: (800) 363-3213

THE TREMCO FAMILY OF PRODUCTS IS RECOGNIZED BY



Tremco Incorporated • 3735 Green Road • Beachwood, Ohio 44122 USA
Phone: (216) 292-5000 • Fax: (216) 514-7575 • Toll Free: (866) 209-2404

Tremco Canada Division • 215 Wicksteed Ave. • Toronto, Ontario M4H 1G7 Canada
Phone: (416) 467-2455 • Fax: (800) 361-3514 • Toll Free: (800) 363-3213

For MSDS or additional Spec Data Sheets, contact customer service at (800) 321-7906 or visit www.tremcofirestop.com

TREMCO