

TREMstop D

A Prefabricated Firestopping Collar Device

PRODUCT DESCRIPTION:

TREMstop D is a pre-fabricated collar device used to firestop nonmetallic pipe penetrations. Installing TREMstop D will save on labor costs associated with the cutting, measuring and installation of the field fabricated TREMstop WS/MCR system. TREMstop D is available in sizes ranging from 1.5 in. to 12 in. (3.8 cm to 30.5 cm) to fit industry standard pipe diameters.

TREMstop D uses an easy fastening system for securing the device around the penetrating item. Simply slip the closure tab through the slit and fold back to fasten. This sealing system is fast and easy to use.

ADVANTAGES:

- Eliminates labor costs associated with cutting, measuring and installation
- Available to fit a wide variety of pipe sizes
- Collar has a green color that makes the device easily identifiable as a Tremco firestopping product
- Quick and easy to fasten: simply slip the closure tab through the slit and fold back to fasten
- Listed up to a 3 hour fire rating

BASIC USES:

Penetrations

- PVC and ccPVC pipe
- ABS and ccABS pipe
- FRPP pipe
- PVDF pipe

Building Assemblies

- Concrete floor or wall
- Wood floor/ceiling
- Gypsum wallboard
- Fluted metal deck
- Hollowcore concrete

PHYSICAL PROPERTIES:

- 26-gauge steel collar
- Powder coated metal
- Collar color: Green

PACKAGING:

| | |
|-----------------------------|---------|
| TREMstop D 1.5 in. (3.8 cm) | 12/case |
| TREMstop D 2 in. (5.1 cm) | 10/case |
| TREMstop D 3 in. (7.6 cm) | 10/case |
| TREMstop D 4 in. (10.2 cm) | 6/case |
| TREMstop D 6 in. (15.2 cm) | 2/case |
| TREMstop D 8 in. (20.3 cm) | 2/case |
| TREMstop D 10 in. (25.4 cm) | 1/case |
| TREMstop D 12 in. (30.5 cm) | 1/case |

Sizes greater than 12 in. (30.5 cm) available upon request. Half sizes appropriate for hubs also available upon request.

TREMstop D

A Prefabricated Firestopping Collar Device

INSTALLATION TECHNIQUES:

Refer to the Tremco Firestopping Products & Systems Guide for firestop systems.

TREMstop D is easily installed by wrapping the device around the penetrating item and securing the hose clamp. Bend the tabs outward and slide the device flush with the wall or floor. Mechanically fasten the TREMstop D with the correct amount of fasteners, symmetrically located, to the building assembly. See firestop system for further detail.

LIMITATIONS:

- Not recommended for passive fire containment systems not listed or approved by Tremco.

APPLICABLE TEST STANDARDS:

UL 1479 (ASTM E-814)
UL 263 (ASTM E-119)
UL 723 (ASTM E-84)
CAN4-S115M
CAN/ULC-S101M

WARRANTY:

Tremco warrants its Firestop Materials to be free of defects, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE with respect to Firestop Materials. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of the Firestop Materials proved to be defective and Tremco shall not be liable for any loss or damage.

TECHNICAL SERVICES

For more information, contact technical services:

Toll free: (866) 209-2404
Fax: (216) 514-7575
E-mail: FireTech@tremcoinc.com

ORDER PLACEMENT:

To place an order, contact customer service:

United States: (800) 321-7906
Canada: (800) 363-3213

THE TREMCO FAMILY OF PRODUCTS IS RECOGNIZED BY



Tremco Incorporated • 3735 Green Road • Beachwood, Ohio 44122 USA
Phone: (216) 292-5000 • Fax: (216) 514-7575 • Toll Free: (866) 209-2404

Tremco Canada Division • 215 Wicksteed Ave. • Toronto, Ontario M4H 1G7 Canada
Phone: (416) 467-2455 • Fax: (800) 361-3514 • Toll Free: (800) 363-3213

For MSDS or additional Spec Data Sheets, contact customer service at (800) 321-7906 or visit www.tremcofirestop.com

TREMCO