

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTGVersion 1.2
REVISION DATE: 07/24/2007

Print Date 07/25/2007

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG
Product code : 907806 333

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Sealant

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

White. Paste. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
Eyes : Slightly irritating.
Ingestion : May cause irritation to the mouth, throat and stomach.
Skin : Irritant effect may be delayed.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Inhalation of crystalline silica (quartz) can cause cancer based on animal data, and IARC concludes sufficient evidence in humans (Group 1). Prolonged and repeated overexposure to free crystalline silica dust above the TLV level may cause scarring of the lungs with cough and shortness of breath. A delayed lung injury, silicosis may result from breathing free silica. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Calcium Carbonate (Limestone)	1317-65-3	40.0 - 70.0
Acrylic Polymer	NJ TSRN# 51721300-5816P	15.0 - 40.0
Water	7732-18-5	15.0 - 40.0
Dipropylene glycol dibenzoate	27138-31-4	5.0 - 10.0
White mineral oil	8042-47-5	3.0 - 7.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	- <1.0
Chlorothalonil	1897-45-6	- <1.0
Formaldehyde	50-00-0	- <0.1

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG

Version 1.2

Print Date 07/25/2007

REVISION DATE: 07/24/2007

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash with water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : Not available.
- Method : Not available.
- Burning rate : Non-flammable solid
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : This product is not expected to burn under normal conditions of use. Use that which is appropriate to the surroundings.
- Hazardous combustion products : Smoke, fumes.
- Protective equipment for firefighters : Not applicable. Product is not expected to burn.
- Fire and explosion conditions : This product not expected to ignite under normal conditions of use.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Scrape up and transfer to appropriate container for disposal. Keep out of water courses.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Do not use in confined or poorly ventilated areas. Store in sealed containers in a dry, ventilated warehouse location above freezing.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION**Personal protection equipment**

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG

Version 1.2

Print Date 07/25/2007

REVISION DATE: 07/24/2007

- Respiratory protection : Not required under normal conditions of use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Use safety glasses if eye contact is likely.
- Protective measures : Use professional judgment in the selection, care, and use. Other equipment not normally required.
- Engineering measures : General ventilation is sufficient. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium Carbonate (Limestone)	1317-65-3	OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Paste
- Color : White
- Odor : Acrylate
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Heavier than air
- Melting point/range : Not available.
- Freezing point : Not available.
- Boiling point/range : Not available.
- Water solubility : Miscible
- Specific Gravity : 1.35
- % Volatile Weight : 16 %

SECTION 10 - REACTIVITY / STABILITY

- Substances to avoid : Oxidizing agents. Strong acids. Strong bases.

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG

Version 1.2

Print Date 07/25/2007

REVISION DATE: 07/24/2007

SECTION 11 - TOXICOLOGICAL INFORMATION

Chlorothalonil, CAS-No.: 1897-45-6

Acute oral toxicity (LD-50 oral) 10,000 mg/kg (Rat)

Acute dermal toxicity (LD-50 dermal) 10,000 mg/kg (Albino rat)

Formaldehyde, CAS-No.: 50-00-0

Acute oral toxicity (LD-50 oral) 800 mg/kg (Rat) 260 mg/kg (Guinea pig) 100 mg/kg (Rat)
42 mg/kg (Mouse)Acute inhalation toxicity (LC-50) 0.82 mg/l for 30 min (Rat) 0.48 mg/l for 4 h (Rat) 0.414
mg/l for 4 h (Mouse) 0.4 mg/l for 2 h (Mouse)**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONSDisposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of
waste in compliance with state and local regulations.**SECTION 14 - TRANSPORTATION / SHIPPING DATA****TDG / DOT Shipping Description:**

NOT REGULATED

SECTION 15 - REGULATORY INFORMATION**North American Inventories:**All components are listed or exempt from the TSCA inventory.
One or more components are listed on the NDSL.**U.S. Federal Regulations:**

SARA 313 Components : Chlorothalonil 1897-45-6

SARA 311/312 Hazards : Acute Health Hazard
Chronic Health Hazard

OSHA Hazardous Components :

Calcium Carbonate (Limestone) 1317-65-3
Crystalline Silica (Quartz)/ Silica Sand 14808-60-7
Chlorothalonil 1897-45-6
Formaldehyde 50-00-0OSHA Status: Considered : Irritant
hazardous based on the Carcinogen
following criteria:

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG

Version 1.2

Print Date 07/25/2007

REVISION DATE: 07/24/2007

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
exempt solvent) : 22 g/l

VOC Method 310 : 1 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

U.S. State Regulations:

MASS RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7
		Formaldehyde	50-00-0
Penn RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Acrylic Polymer	NJ TSRN# 51721300-5816P
		Water	7732-18-5
		Dipropylene glycol dibenzoate	27138-31-4
		White mineral oil	8042-47-5
		Formaldehyde	50-00-0
NJ RTK Components	:	Calcium Carbonate (Limestone)	1317-65-3
		Acrylic Polymer	NJ TSRN# 51721300-5816P
		Water	7732-18-5
		Dipropylene glycol dibenzoate	27138-31-4
		White mineral oil	8042-47-5
		Crystalline Silica (Quartz)/ Silica Sand	14808-60-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

14808-60-7	Crystalline Silica (Quartz)/ Silica Sand
1897-45-6	Chlorothalonil
50-00-0	Formaldehyde
64-17-5	Ethyl alcohol

SECTION 16 - OTHER INFORMATION**HMIS Rating :**

Health	2
Flammability	1
Reactivity	0
PPE	

0 = Minimum
1 = Slight
2 = Moderate
3 = Serious
4 = Severe

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

TREMFLEX 834 SMOKE&SOUND WHITE-12 QT CTG

Version 1.2

Print Date 07/25/2007

REVISION DATE: 07/24/2007

Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System